

Construction Receivers

Apache Bullseye 3+ Machine Control Laser Receiver

Alkaline — #ATI991340-02 (Red) or #ATI991340-09 (Yellow)

NiMH — #ATI991346-02 (Red) or #ATI991346-09 (Yellow)

Adapts to grading and excavating machinery - Use on dozers, graders, scrapers, and box blades.

Super bright LED's with green on-grade are easy to see in all light conditions.

Easy to move from one machine to another.

3 selectable accuracies - work from rough grading to final finishing.

5 channels of grade information plus directional out of beam indicators.

Use as a stand alone display receiver or combine with the optional RD15 Remote Display #4851-010. Available in red or yellow.



Apache Bullseye 5+ Machine Control Laser Receiver

Alkaline — #ATI991370-02 (Red) or #ATI991370-09 (Yellow)

NiMH — #ATI991376-02 (Red) or #ATI991376-09 (Yellow)

Built-in blade tilt indication helps the operator keep the blade level or the stick plumb for increased production and accuracy. It can be programmed to match an existing or known grade for slope matching operations.

Center On-grade provides an equal amount of grade information above and below on-grade. Use on dozers, graders, scrapers, backhoes, excavators, trenchers, scrapers, and box blades. Plumb indication is built in for quick and accurate grade checking.

Offset On-grade provides more information above grade utilizing the entire receiver for productive excavation. Three selectable accuracies for each on-grade location and up to six channels of grade information plus directional out of beam indicators.

Use as a stand alone display receiver or combine with the optional RD15 Remote Display #4851-010. Available in red or yellow.



Apache Bullseye 6 Machine Control Laser Receiver

Alkaline — #ATI991320-02 (Red) or #ATI991320-09 (Yellow)

NiMH — #ATI991326-02 (Red) or #ATI991326-09 (Yellow)

Angle compensation automatically calculates and corrects the grade display for the angle of the dipper arm. Check grade with the dipper arm extended or retracted up to 30 degrees. Plumb indication built in - for quick and accurate grade checking for excavators and backhoes.

Center On-grade - for grading operations - use on dozers, graders, scrapers, box blades. Offset On-grade - for productive excavation.

4 selectable accuracies for each on-grade location.

Up to 8 channels of grade information plus directional out of beam indicators.

Use as a stand alone display receiver or combine with the optional RD15 Remote Display #4851-010. Available in red or yellow.



Apache Bullseye Remote Display

#ATI991570-02 (Red)

#ATI991570-09 (Yellow)

The Remote Display can be used with all Bullseye™ receivers with an accessory connector.

The remote display allows the operator to view grade information in the cab when it is not otherwise convenient.

The LED's mimic the receiver display.

The remote display is an ideal solution when the receiver is behind the operator such as in trenchers, box blades, scrapers, etc.

Power and signal are drawn from the receiver using either of the required cables (below).

The remote can be powered by the machine with one of the remote power cables (below).

Available in red or yellow.



*Shown with the optional
#ATIo10976-02 Swivel
Mount*

Number:	Required cable — Select one:
#ATIo10972-15	Receiver cable, straight, 15 ft
#ATIo10972-20	Receiver cable, straight, 20 ft
#ATIo10972-25	Receiver cable, straight, 25 ft
#ATIo10972-30	Receiver cable, straight, 30 ft
#ATIo10972-35	Receiver cable, straight, 35 ft
#ATIo10972-40	Receiver cable, straight, 40 ft
#ATIo10972-50	Receiver cable, straight, 50 ft
#ATIo10973	Receiver cable, coil, 3-12 ft
Optional cables:	
#ATIo10983	Machine power cable, lighter adapter, 2-8 ft
#ATIo10987	Machine power cable, ring terminals, 25 ft
#ATIo10975	Receiver cable extension, coil, 3-12 ft
#ATIo10988-10	Receiver cable extension, straight, 10 ft
#ATIo10988-15	Receiver cable extension, straight, 15 ft
#ATIo10988-20	Receiver cable extension, straight, 20 ft
#ATIo10988-35	Receiver cable extension, straight, 35 ft

Apache Bullseye Magnetic Mounts & Receiver Accessories

#ATI991360-02 (top)

This magnetic mount can be used with all Bullseye receivers.

Two magnet banks combine for 900 pounds of holding force. Easy removal is accomplished using a release lever.

Features include a large vertical adjustment range for quicker laser set-ups.

It is easy to slide the receiver up and down.

Ideal for quick installation on backhoes and excavators.

#ATI991364-02 (bottom)

This magnet mount can be used with all Bullseye receivers.

The magnet banks attach to flat back dozer blades.

Ideal for lighter duty applications.



Number:	Other Bullseye Receiver Accessories:
#ATI991604	Universal battery charger with wall plugs
#ATIo10542	Cannon adapter for charger
#ATIo10561	Car lighter adapter, 12-volt DC
#ATIo10562	C-Cell NiMH HD Rechargeable Battery
#ATIo10563-02S	Bullseye carrying case (Red)
#ATIo10536-09S	Bullseye carrying case (Yellow)
#ATIo10976-02	Swivel mount (shown above, left)