

METAL FINDER

MetalliScanner® MT 6



SPECIFICATIONS

Dimensions	8.87 in. H x 3.84 in. W x 2.23 in. D (225 mm x 98 mm x 57 mm)
Weight	10.1 oz. (286 g) without battery
Battery Type	9-V alkaline (not included)
Position Accuracy	Center of #4 (½ in.) rebar or ½ in. (13 mm) copper pipe at a minimum grid spacing of 6 in. (152 mm) typically within ½ in. (13 mm)
Depth	Up to 6 in. (152 mm) ± 1 in. (25 mm)
Operating Temperature	20° to 120°F (-7° to 49°C)
Storage Temperature	-20° to 150°F (-29° to 66°C)
Humidity	80% RH (noncondensing)
Water Resistance	Splash and water resistant, not waterproof

Electronic Metal Locator

Locate embedded metal before your drill bit or saw blade does. This powerful dedicated metal scanning tool can locate metal up to 6 inches deep in solid concrete.

MetalliScanner® MT 6 locates both ferrous and non-ferrous metal up to 6 inches (152 mm) deep in concrete and other non-metallic surfaces. It also differentiates between ferrous and non-ferrous metal targets and indicates the target depth in inches and centimeters.

MT 6 indicates when you are approaching a metal object with a large plus (+) sign on the display. When the plus becomes a minus (-), you have crossed over the target and are now moving away.

Use MetalliScanner® MT 6 to find or avoid rebar, cables, pipe, nails in reclaimed wood, nails/tacks in studs behind lath & plaster walls, electrical boxes and conduit, and more.

MetalliScanner® MT 6 is the tool recommended by the My Safe Florida Home Program to assist in hurricane loss mitigation.

- Automatically differentiates between magnetic metal (such as rebar) and non-magnetic metal (such as copper pipe)
- Shows the depth of metal from the surface in both inches and centimeters
- Easy-to-read LCD screen pinpoints the location of metal objects to the nearest ½ inch (13 mm) and depth to the nearest inch (25 mm)
- Helps map out the grid of metal through any nonmetallic construction material, including concrete, tile, and marble



Scan for Metal